

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION

© COPYRIGHT ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
J		P	LTR	DESCRIPTION	DATE	DWN	APVD
			A3	REVISED	FJ00-2017-00	21DEC00	N.Y N.S
			B	REVISED	ECR-06-024409	13NOV06	SK SI
			BI	REVISED	ECR-12-019260	08NOV12	TS KB

1. INSTRUCTION SHEET ; 411-5919
2. DOUBLE LOCK SHOULD BE SET TO THE PRE-ASSEMBLY POSITION WITHIN THE PLUG HOUSING WHEN SHIPPED TO THE CUSTOMER.
3. DETAILS OF CAVITIES;SEE TABLE-1.

1. 取扱説明書 ; 411-5919
2. ダブルロックは、仮係止状態で出荷される。
3. キャビティ構成はTABLE-1参照。

	FINISH	POS. 極数	P/N	APPLICABLE WIRE RANGE 適用電線
SIGNAL .025	TIN	5	1123343-1	AVSS 0.3-0.5mm <sup>2</sup> CAVS0.3-0.5 mm <sup>2</sup> CAVUS 0.3-0.5mm <sup>2</sup> AVSSH 0.3-0.5mm <sup>2</sup>
POWER .040	TIN	2	316836-1	AVS 0.3-0.5mm <sup>2</sup> AVSS/CAVS 0.3-0.85mm <sup>2</sup> CAVUS 0.3-0.85mm <sup>2</sup>
			316838-1	AVS 0.5mm <sup>2</sup> AVSS/CAVS 0.85-1.25mm <sup>2</sup> CAVUS 1.25mm <sup>2</sup>

BLACK	1318801-1
COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN N. YASUDA 07JUL99	TE Connectivity	
DIMENSIONS: 単位: 概 mm		CHK N. SAI 07JUL99		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 = ± 0.2		APVD N. SAI 07JUL99		
0-PLC ± 1-PLC ±0.1 2-PLC ±0.01 3-PLC ±0.001 4-PLC ±0.0001 ANGLES ±3°		NAME 025/040 7P PLUG HOUSING, IMMOBILIZER		
MATERIAL 材料 PBT		FINISH 仕上 BLACK	PRODUCT SPEC 製品規格 108-5664	SIZE A3
		APPLICATION SPEC 取付適用規格 114-5217,5250	WEIGHT 1.47 g	CAGE CODE 00779
		RESTRICTED CUSTOMER	SCALE 尺度 3:1	DRAWING NO 番号 C-1318801
				RESTRICTED TO
				SHEET 1 OF 1
				REV BI

1470-19 (3/11)